



中国认可
国际互认
检测
TESTING
CNAS L0446



Page 1 of 8

Test Report

Verified code: 329803

Report No.: E20220818423001-4

Customer: Lumi United Technology Co., Ltd

Address: Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No.3370, Liuxian Avenue, Fuguang Community, Taoyuan Residential District, Nanshan District, Shenzhen, China

Sample Name: Smart Video Doorbell G4

Sample Model: SVD-C01

Receive Sample Date: Aug.19,2022

Test Date: Aug.19,2022 ~ Oct.14,2022

Reference Document: EN 50665:2017

Test Result: Pass

Prepared by: *Huang Lifang*

Reviewed by:

Wu Haoting

Approved by:

Xiao Liang

GUANGZHOU GRG METROLOGY & TEST CO., LTD

Issued Date: 2022-11-30

GUANGZHOU GRG METROLOGY & TEST CO., LTD.

Address: No.163,Pingyun Road, West of Huangpu Avenue, Guangzhou, Guangdong, China
Tel: (+86) 400-602-0999 FAX: (+86) 020-38698685 Web: <http://www.grgtest.com>



Statement

1. The report is invalid without "special seal for inspection and testing"; some copies are invalid; The report is invalid if it is altered or missing; The report is invalid without the signature of the person who prepared, reviewed and approved it.
2. The sample information is provided by the client and responsible for its authenticity; The content of the report is only valid for the samples sent this time.
3. When there are reports in both Chinese and English, the Chinese version will prevail when the language problems are inconsistent.
4. If there is any objection concerning the report, please inform us within 15 days from the date of receiving the report.
5. Without the agreement of the laboratory, the client is not authorized to use the test results for unapproved propaganda.

----- The following blanks -----

TABLE OF CONTENTS

1.	GENERAL DESCRIPTION OF EUT	5
1.1	APPLICANT INFORMATION.....	5
1.2	MANUFACTURER	5
1.3	BASIC DESCRIPTION OF EUT	5
2.	LABORATORY	6
3.	ACCREDITATIONS.....	6
4.	TECHNICAL REQUIREMENTS SPECIFICATION IN	7
4.1	RF EXPOSURE EVALUATION	7
4.2	EVALUATION RESULTS	8

----- The following blanks -----

REPORT ISSUED HISTORY

Report Version	Report No.	Description	Compile Date
1.0	E20220818423001-4	Original Issue	2022-10-14

----- The following blanks -----

1. GENERAL DESCRIPTION OF EUT

1.1 APPLICANT INFORMATION

Name: Lumi United Technology Co., Ltd
Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No.3370, Liuxian Avenue, Fuguang Community, Taoyuan Residential District, Nanshan District, Shenzhen, China

Address: Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No.3370, Liuxian Avenue, Fuguang Community, Taoyuan Residential District, Nanshan District, Shenzhen, China

1.2 MANUFACTURER

Name: Lumi United Technology Co., Ltd
Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No.3370, Liuxian Avenue, Fuguang Community, Taoyuan Residential District, Nanshan District, Shenzhen, China

Address: Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No.3370, Liuxian Avenue, Fuguang Community, Taoyuan Residential District, Nanshan District, Shenzhen, China

1.3 BASIC DESCRIPTION OF EUT

Product Name: Smart Video Doorbell G4

Product Model: SVD-C01

Adding Model: SVD-C03

Models Difference: that EUT (Smart Video Doorbell G4) Model Numbers SVD-C01 and SVD-C03 have the same technical construction including circuit diagram,PCB LAYOUT,hardware version and software version identical,except color of enclosures and sales method are different.

Trade Name: Aqara

Power Supply: AC 12-24V power supplied by AC power convert
DC 8-24V power supplied by DC adapter
DC 4.5V power supplied by battery

Frequency Band: 2412MHz-2472MHz for 802.11b/g/n HT20

Antenna Specification: FPC antenna with 0.5dBi gain (Max)

Hardware Version: T0

Software Version: 1.0.4_0010

Sample submitting way: Provided by customer Sampling

Sample No: E20220818423001-0001, E20220818423001-0003

Note: /

2. LABORATORY

The tests & measurements refer to this report were performed by Shenzhen EMC Laboratory of Guangzhou GRG Metrology & Test Co., Ltd.

Add.: No.1301 Guanguang Road Xinlan Community, Guanlan Street, Longhua District
Shenzhen, 518110, People's Republic of China.
P.C.: 518110
Tel : 0755-61180008
Fax: 0755-61180008

3. ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to GB/T 27025(ISO/IEC 17025:2017)

USA A2LA(Certificate #2861.01)

China CNAS(L0446)

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada ISED (Company Number: 24897, CAB identifier:CN0069)

USA FCC (Registration Number: 759402, Designation Number:CN1198)

Copies of granted accreditation certificates are available for downloading from our web site,
<http://www.grgtest.com>

----- The following blanks -----

4. TECHNICAL REQUIREMENTS SPECIFICATION IN

4.1 RF EXPOSURE EVALUATION

This European Standard applies to electronic and electrical equipment for which no dedicated Harmonized product – or product family standard, or standard relating to low power equipment, regarding human exposure not. Annex A lists such harmonized standards available at the time of writing This list may change with time. The current list of standards harmonized under each directive should be consulted at the time of use of this standard.

The measurements and calculations to demonstrate equipment compliance shall be made according to EN 62311:2008, Clause 4 and 5. The general considerations as defined in EN 62311:2008, Clause 4 and 5 shall apply to all equipment.

The product is deemed to fulfil the requirements of this standard if the calculated and/or measured values are less than or equal to the limits.

NOTE In the setting of basic restrictions and the derived reference levels, safety factors have been taken into account. In the specification of the assessment method, uncertainty has been constrained. This is the reason for not requiring that the measured values shall be compared to the limit reduced by the measurement uncertainty.

Reference levels for electric, magnetic and electromagnetic fields
(0 Hz to 300 GHz, unperturbed rms values)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (μT)	Equivalent plane wave power density S_{eq} (W/m ²)
0-1 Hz	—	$3,2 \times 10^4$	4×10^4	—
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	—
8-25 Hz	10 000	$4\,000/f$	$5\,000/f$	—
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	—
0,8-3 kHz	$250/f$	5	6,25	—
3-150 kHz	87	5	6,25	—
0,15-1 MHz	87	$0,73/f$	$0,92/f$	—
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	—
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10

Notes

- f as indicated in the frequency range column.
- For frequencies between 100 kHz and 10 GHz, S_{eq} , E^2 , H^2 , and B^2 are to be averaged over any six-minute period.
- For frequencies exceeding 10 GHz, S_{eq} , E^2 , H^2 , and B^2 are to be averaged over any $68/f^{1.05}$ -minute period (f in GHz).
- No E-field value is provided for frequencies < 1 Hz, which are effectively static electric fields. For most people the annoying perception of surface electric charges will not occur at field strengths less than 25 kV/m. Spark discharges causing stress or annoyance should be avoided.

4.2 EVALUATION RESULTS

Exposure Restrictions						
Mode	Max. Output Power (dBm)	Gain (dBi)	EIRP Power (dBm)	Frequency Band(MHz)	Power Density (W/m ²)	Limit of Power Density (W/m ²)
2.4GWIFI-802.11b	15.05	0.5	15.55	2412-2472	0.07144	10
2.4GWIFI-802.11g	12.59	0.5	13.09		0.04055	10
2.4GWIFI-802.11n HT20	12.5	0.5	13.00		0.03971	10

Note:

1.The maximum output Power were refer to the RF report.

2.The field calculation does not take into account the antenna size, which is assumed to be a point source. An ideal isotropic antenna is used as a reference to compare the performance of practical antennas: P watts is radiated, from a point, uniformly over the surface of sphere of radius R . Assumed use distance from EUT to Human, **20 cm** separation distance warning is required.

The Formula

$$S = \frac{P}{4\pi R^2}$$

Whereas,

S = power density

R=distance from observation point to the antenna (m)

P= The maximum e.i.r.p of the transmitter (W) .

In this section, the power density at 20 cm location is calculated to examine if it is lower than the limit.

The worst case:

Max. 2.4G WIFI = 0.07144(W/m²) < 10(W/m²)

The test result is passed.

----- End of Report -----