


Prüfbericht-Nr.: <i>Test report no.:</i>	CN21IXUA 001	Auftrags-Nr.: <i>Order no.:</i>	170259209	Seite 1 von 41 Page 1 of 41
Kunden-Referenz-Nr.: <i>Client Reference No.:</i>	N/A	Auftragsdatum: <i>Order date.:</i>	2020.12.29	
Auftraggeber: <i>Client:</i>	Lumi United Technology Co., Ltd. 8th Floor, JinQi Wisdom Valley, No.1 Tangling Road, Liuxian Ave, Taoyuan Residential District, Nanshan District, Shenzhen, Guangdong, P.R. China			
Prüfgegenstand: <i>Test item:</i>	Smart Wall Switch			
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	WS-EUK03, WS-EUK04			
Auftrags-Inhalt: <i>Order content:</i>	TÜV Rheinland RED service			
Prüfgrundlage: <i>Test specification:</i>	EN 300328 V2.2.2:2019 EN 301 489-1 V2.2.3:2019 EN IEC 61000-3-2:2019 EN 60669-1:1999+A1+A2	EN IEC 62311:2010 EN 301 489-17 V3.2.4:2020 EN 61000-3-3:2013+A1 EN 60669-2-1:2004+A1+A12		
Wareneingangsdatum: <i>Date of sample receipt:</i>	2020.12.31			
Prüfmuster-Nr.: <i>Test sample No.:</i>	A002979252 005			
Prüfzeitraum: <i>Testing period:</i>	Refer to test report			
Ort der Prüfung: <i>Place of testing:</i>	Refer to section 2.1			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Guangdong) Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
überprüft von: <i>reviewed by:</i>	<i>Amy Wang</i>		genehmigt von: <i>authorized by:</i>	<i>Storm Shu</i>
Datum: 2021.03.12 <i>Date:</i>			Datum: 2021.03.22 <i>Date:</i>	
Stellung/Position:	Amy Wang/Project Manager		Stellung/Position:	Storm Shu/TC
Sonstiges / Other:	<p>They are for compliance with all provisions in the Article 3 of Council Directive 2014/53/EU referred to as the RED. This report is for Article 3.2 Radio Spectrum, Article 3.1a Health requirements and Article 3.1b EMC only. Please refer to the related test report about essential requirements for details as below, TUV Rheinland report: CN21U8UU 001 (Article 3.1b EMC) TUV Rheinland report: CN21SO31 001 (Article 3.1a electrical safety).</p>			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	1 = sehr gut 2 = gut P(ass) = entspricht o.g. Prüfgrundlage(n)	3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	4 = ausreichend N/A = nicht anwendbar	5 = mangelhaft N/T = nicht getestet
Legend:	1 = very good 2 = good P(ass) = passed a.m. test specifications(s)	3 = satisfactory F(ail) = failed a.m. test specifications(s)	4 = sufficient N/A = not applicable	5 = poor N/T = not tested
<p>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i></p>				

Test Summary

5.1.1 RF OUTPUT POWER

RESULT: Pass

5.1.2 POWER SPECTRAL DENSITY

RESULT: Pass

5.1.3 DUTY CYCLE, TX-SEQUENCE, TX-GAP

RESULT: Pass

5.1.4 MEDIUM UTILISATION (MU) FACTOR

RESULT: Pass

5.1.5 ADAPTIVITY

RESULT: Not applicable

5.1.6 OCCUPIED CHANNEL BANDWIDTH

RESULT: Pass

5.1.7 TRANSMITTER UNWANTED EMISSIONS IN THE OUT-OF-BAND DOMAIN

RESULT: Pass

5.1.8 TRANSMITTER UNWANTED EMISSIONS IN THE SPURIOUS DOMAIN

RESULT: Pass

5.2.1 RECEIVER SPURIOUS EMISSIONS

RESULT: Pass

5.2.2 RECEIVER BLOCKING

RESULT: Pass

5.2.3 GEO-LOCATION CAPABILITY

RESULT: Not applicable

6.1.1 HARMONIC CURRENT EMISSIONS ON AC MAINS

RESULT: Pass

6.1.2 VOLTAGE FLUCTUATIONS AND FLICKER ON AC MAINS

RESULT: Pass

6.1.3 CONDUCTED EMISSION ON AC MAINS

RESULT: Pass

6.1.4 CONDUCTED EMISSION ON DC POWER INPUT/OUTPUT PORT

RESULT: Not applicable

6.1.5 CONDUCTED EMISSION ON WIRED NETWORK PORT

RESULT: Not applicable

6.1.6 RADIATED EMISSION

RESULT: Pass

6.2.1 RADIO FREQUENCY ELECTROMAGNETIC FIELDS (RS)

RESULT: Pass

6.2.2 RADIO FREQUENCY CONTINUOUS CONDUCTED (CS)

RESULT: Pass

6.2.3 ELECTROSTATIC DISCHARGE (ESD)

RESULT: Pass

6.2.4 ELECTRICAL FAST TRANSIENTS (EFT)

RESULT: Pass

6.2.5 SURGE

RESULT: Pass

6.2.6 VOLTAGE DIPS AND INTERRUPTIONS

Prüfbericht - Nr.: CN21IXUA 001
Test Report No.

Seite 3 von 41
Page 3 of 41

RESULT: Pass

7.1.1 ELECTROMAGNETIC FIELDS

RESULT: Pass

Contents

1	GENERAL REMARKS	6
1.1	COMPLEMENTARY MATERIALS	6
2	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	UNCERTAINTY OF MEASUREMENT.....	7
3	GENERAL PRODUCT INFORMATION	8
3.1	PRODUCT FUNCTION AND INTENDED USE.....	8
3.2	RATINGS AND SYSTEM DETAILS	8
3.3	INDEPENDENT OPERATION MODES	9
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	9
3.5	SUBMITTED DOCUMENTS.....	9
4	TEST SET-UP AND OPERATION MODES	10
4.1	PRINCIPLE OF CONFIGURATION SELECTION	10
4.2	TEST OPERATION AND TEST SOFTWARE	10
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	10
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	10
5	TEST RESULTS ERM	11
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	11
5.1.1	<i>RF Output Power.....</i>	<i>11</i>
5.1.2	<i>Power Spectral Density.....</i>	<i>12</i>
5.1.3	<i>Duty Cycle, TX-sequence, TX-gap.....</i>	<i>13</i>
5.1.4	<i>Medium Utilisation (MU) Factor.....</i>	<i>14</i>
5.1.5	<i>Adaptivity</i>	<i>15</i>
5.1.6	<i>Occupied Channel Bandwidth.....</i>	<i>16</i>
5.1.7	<i>Transmitter Unwanted Emissions in the Out-of-band Domain.....</i>	<i>17</i>
5.1.8	<i>Transmitter Unwanted Emissions in the Spurious Domain.....</i>	<i>18</i>
5.2	RECEIVER REQUIREMENT & TEST SUITES	19
5.2.1	<i>Receiver Spurious Emissions</i>	<i>19</i>
5.2.2	<i>Receiver Blocking.....</i>	<i>20</i>
5.2.3	<i>Geo-location Capability.....</i>	<i>21</i>
6	TEST RESULTS OF EMC REQUIREMENT.....	21
6.1	TEST RESULTS OF EMISSION	22
6.1.1	<i>Harmonic Current Emissions on AC Mains.....</i>	<i>22</i>
6.1.2	<i>Voltage Fluctuations and Flicker on AC Mains</i>	<i>23</i>
6.1.3	<i>Conducted Emission on AC Mains.....</i>	<i>24</i>
6.1.4	<i>Conducted Emission on DC power input/output port</i>	<i>25</i>
6.1.5	<i>Conducted Emission on Wired network port.....</i>	<i>25</i>
6.1.6	<i>Radiated Emission</i>	<i>26</i>
6.2	TEST RESULTS OF IMMUNITY.....	27
6.2.1	<i>Radio Frequency Electromagnetic Fields (RS).....</i>	<i>27</i>
6.2.2	<i>Radio Frequency Continuous Conducted (CS).....</i>	<i>28</i>

6.2.3	<i>Electrostatic Discharge (ESD)</i>	29
6.2.4	<i>Electrical Fast Transients (EFT)</i>	30
6.2.5	<i>Surge</i>	31
6.2.6	<i>Voltage Dips and Interruptions</i>	32
7	SAFETY HUMAN EXPOSURE	33
7.1	HUMAN EXPOSURE TO ELECTROMAGNETIC FIELDS 10MHZ-300GHZ	33
7.1.1	<i>Electromagnetic Fields</i>	33
8	PHOTOGRAPHS OF THE TEST SET-UP	34
9	LIST OF TABLES	41
10	LIST OF PHOTOGRAPHS	41

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:
Appendix 1: Test Results of Article 3.2 Radio Spectrum Requirements and Article 3.1b EMC Requirements.
Appendix 1: List of Test and Measurement Equipment and test result.

2 Test Site

2.1 Test Facilities

Waltek Testing Group (Shenzhen) Co., Ltd.

1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

The tests at the test sites have been conducted under the supervision of a TÜV engineer.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Refer to attached Appendix 1.

2.3 Uncertainty of Measurement

Table 2: Measurement Uncertainty

Parameter	Uncertainty
Output Power	±0.42dB
Occupied Channel Bandwidth	±1.5%
Power Spectral Density	±0.70 dB
Conducted Spurious Emission	±2.17 dB
Conducted Emission	9KHz-150KHz ±3.74dB 150 KHz ~ 30MHz ±3.34dB
Radiated Emissions	30-200MHz ±4.52dB 0.2-1GHz ±5.56dB 1-6GHz ±3.84dB 6-18GHz ±3.92dB
Temperature	±0.88°C
Time	±0.58 %
Supply voltages	±0.3 %
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3 General Product Information

The submitted samples WS-EUK03 and WS-EUK04 are Smart Wall Switch with ZigBee wireless control for household used.

Model WS-EUK03 and WS-EUK04 have the same electronic designed and wireless module except for the structure. WS-EUK04 has two control loops, WS-EUK03 has one control loop.

Based on above information, full RF tests were performed on model WS-EUK04.

For details, refer to the User Manual, Technical Description and Circuit Diagram.

3.1 Product Function and Intended Use

Refer to the Technical Documentation and user manual.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment	Smart Wall Switch
Type Designation	WS-EUK03, WS-EUK04
Type of Device	DSSS with non-adaptive
Classification of Receiver	Category 2
Operating Temperature Range	-10 °C ~ +40 °C
Operating Voltage	AC 100-250V, 50/60Hz, Max. 8A (Resistive Load), 50/60Hz
Testing Voltage	AC 230V, 50Hz
Technical Specification of Wi-Fi Wireless	
Operating Frequency	2405 - 2480 MHz
Type of Modulation	O-QPSK
Channel Number	16
Channel Spacing	5MHz
Antenna Type	PIFA Antenna
Antenna Gain	1dBi

Table 4: RF Channel and Frequency of General 2.4GHz Wireless

RF Channel	ZigBee
	Frequency (MHz)
11	2405
12	2410
13	2415
14	2420
15	2425
16	2430
17	2435
18	2440
19	2445
20	2450
21	2455
22	2460
23	2465
24	2470
25	2475
26	2480

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, wireless
 - 1. Transmitting mode
 - a. Low channel
 - b. Middle channel
 - c. High channel
 - 2. Receiving mode
 - a. Low channel
 - b. High channel
- B. On, Operating on normal mode (communication data through wireless link)
- C. Off

3.4 Noise Generating and Noise Suppressing Parts

For details refer to the Circuit Diagram.

3.5 Submitted Documents

- PCB Layout
- Schematics
- User Manual
- Parts List
- Rating Label
- Model Difference Letter

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Immunity: The equipment under test (EUT) was configured to have its highest possible susceptibility against the tested phenomena. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Software used for testing: pca10028v20191217

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed in section 3.3 as appropriate, the connection laptop was removed when performing the testing.

Test operation refers to test setup in chapter 5 and chapter 6.

4.3 Special Accessories and Auxiliary Equipment

Table 5: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Notebook	Lenovo	E445	EB12648265	N/A
Mobile phone	HUAWEI	VOG-AL00	N/A	N/A
Hub M1S	Lumi	HM1S-G01	N/A	N/A

4.4 Countermeasures to Achieve EMC Compliance

No additional measures were employed to achieve compliance.

5 Test Results ERM

5.1 Transmitter Requirement & Test Suites

5.1.1 RF Output Power

RESULT:

Pass

Test Specification

Test standard	: EN 300 328 V2.2.2
Test requirement	: EN 300 328 V2.2.2, Clause 4.3.2.2
Limit	: EN 300 328 V2.2.2, Clause 4.3.2.2.3
Test suites	: EN 300 328 V2.2.2, Clause 5.4.2

Test Setup

Date of testing	: 2021.01.29
Test voltage	: AC230V
Test environment	: Normal and extreme temperature
Operation mode	: A.1
Ambient temperature	: 20 °C
Relative humidity	: 46 %
Atmospheric pressure	: 101 kPa

Table 6: Test Result of RF Output Power

TEST CONDITIONS	Total e.i.r.p (dBm)		
	Low	Middle	High
25°C	11.22	11.14	10.94
-10°C	11.19	11.11	10.92
40°C	11.20	11.13	10.93
Max e.i.r.p Power	11.22		
Limits	20dBm		
Result	Complies		

NOTE:

- The cable loss is taken into account in results.
- The RF Output Power (P) should be calculated using the formula below:
The $P = A_{(RMS\ power)} + G + Y$
Antenna gain(G): 1.0 dBi

5.1.2 Power Spectral Density

RESULT:

Pass

Test Specification

Test standard : EN 300 328 V2.2.2
 Test requirement : EN 300 328 V2.2.2, Clause 4.3.2.3
 Limit : EN 300 328 V2.2.2, Clause 4.3.2.3.3
 Test suites : EN 300 328 V2.2.2, Clause 5.4.3

Test Setup

Date of testing : 2021.01.29
 Test voltage : AC230V
 Test environment : Normal temperature
 Operation mode : A.1
 Ambient temperature : 24 °C
 Relative humidity : 53 %
 Atmospheric pressure : 101 kPa

Table 7: Test Result of Power Spectral Density

Modulation	Frequency (MHz)	RF Output Power (dBm)	Limit(s) (dBm)	Result
ZigBee	L(2405)	9.95	≤ 10dBm/MHz	Pass
	M(2440)	9.85		Pass
	H(2480)	9.69		Pass
Maximum Measured Value		9.95		Pass

NOTE:

- The cable loss is taken into account in results.
- The Power Spectral Density (PSD) should be calculated using the formula below:
 The $PSD = D + G + Y + 10 \times \log(1/DC)$ (dBm/MHz)
 Antenna gain(G): 1.0 dBi

For the measurement records, refer to the appendix 1.

5.1.3 Duty Cycle, TX-sequence, TX-gap

RESULT:

Pass

Test Specification

Test standard	: EN 300 328 V2.2.2
Test requirement	: EN 300 328 V2.2.2, Clause 4.3.2.4
Limit	: EN 300 328 V2.2.2, Clause 4.3.2.4.3
Test suites	: EN 300 328 V2.2.2, Clause 5.4.2

Test Setup

Date of testing	: 2021.01.29
Test voltage	: AC230V
Test environment	: Normal temperature
Operation mode	: B
Ambient temperature	: 20 °C
Relative humidity	: 46%
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix 1.

5.1.4 Medium Utilisation (MU) Factor

RESULT:

Pass

Test Specification

Test standard	: EN 300 328 V2.2.2
Test requirement	: EN 300 328 V2.2.2, Clause 4.3.2.5
Limit	: EN 300 328 V2.2.2, Clause 4.3.2.5.3
Test suites	: EN 300 328 V2.2.2, Clause 5.4.2

Test Setup

Date of testing	: 2021.01.29
Test voltage	: AC230V
Test environment	: Normal temperature
Operation mode	: C
Ambient temperature	: 20 °C
Relative humidity	: 46%
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix 1.

5.1.5 Adaptivity

RESULT:

Not applicable

Test Specification

Test standard	: EN 300 328 V2.2.2
Test requirement	: EN 300 328 V2.2.2, Clause 4.3.2.6
Limit	: EN 300 328 V2.2.2, Clause 4.3.2.6.2.2
Test suites	: EN 300 328 V2.2.2, Clause 5.4.6

Exemption Conditions:

These requirements apply to non-adaptive equipment or to adaptive equipment when operating in non-adaptive mode. The equipment is using wide band modulations other than FHSS.

Conclusion

The EUT is non-adaptive equipment, hence this requirement is not applicable.

5.1.6 Occupied Channel Bandwidth

RESULT:

Pass

Test Specification

Test standard	: EN 300 328 V2.2.2
Test requirement	: EN 300 328 V2.2.2, Clause 4.3.2.7
Limit	: EN 300 328 V2.2.2, Clause 4.3.2.7.3
Test suites	: EN 300 328 V2.2.2, Clause 5.4.7

Test Setup

Date of testing	: 2021.01.29
Test voltage	: AC230V
Test environment	: Normal temperature
Operation mode	: A.1
Ambient temperature	: 21 °C
Relative humidity	: 46 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix 1.

5.1.7 Transmitter Unwanted Emissions in the Out-of-band Domain

RESULT:

Pass

Test Specification

Test standard	: EN 300 328 V2.2.2
Test requirement	: EN 300 328 V2.2.2, Clause 4.3.2.8
Limit	: EN 300 328 V2.2.2, Clause 4.3.2.8.3
Test suites	: EN 300 328 V2.2.2, Clause 5.4.7

Test Setup

Date of testing	: Refer to the appendix 1
Test voltage	: AC230V
Test environment	: Normal temperature
Operation mode	: A.1
Ambient temperature	: Refer to the appendix 1
Relative humidity	: Refer to the appendix 1
Atmospheric pressure	: Refer to the appendix 1

For the measurement records, refer to the appendix 1.

5.1.8 Transmitter Unwanted Emissions in the Spurious Domain

RESULT:

Pass

Test Specification

Test standard	: EN 300 328 V2.2.2
Test requirement	: EN 300 328 V2.2.2, Clause 4.3.2.9
Limit	: EN 300 328 V2.2.2, Clause 4.3.2.9.3
Test suites	: EN 300 328 V2.2.2, Clause 5.4.9

Test Setup

Date of testing	: Refer to the appendix 1
Test voltage	: AC230V
Test environment	: Normal temperature
Operation mode	: A.1
Ambient temperature	: Refer to the appendix 1
Relative humidity	: Refer to the appendix 1
Atmospheric pressure	: Refer to the appendix 1

For the measurement records, refer to the appendix 1.

Prüfbericht - Nr.: CN21IXUA 001

Test Report No.

Seite 19 von 41

Page 19 of 41

5.2 Receiver Requirement & Test Suites

5.2.1 Receiver Spurious Emissions

RESULT:

Pass

Test Specification

Test standard	: EN 300 328 V2.2.2
Test requirement	: EN 300 328 V2.2.2, Clause 4.3.2.10
Limit	: EN 300 328 V2.2.2, Clause 4.3.2.10.3
Test suites	: EN 300 328 V2.2.2, Clause 5.4.10

Test Setup

Date of testing	: Refer to the appendix 1
Test voltage	: AC230V
Test environment	: Normal temperature
Operation mode	: A.2
Ambient temperature	: Refer to the appendix 1
Relative humidity	: Refer to the appendix 1
Atmospheric pressure	: Refer to the appendix 1

For the measurement records, refer to the appendix 1.

5.2.2 Receiver Blocking

RESULT:

Pass

Test Specification

Test standard	:	EN 300 328 V2.2.2
Test requirement	:	EN 300 328 V2.2.2, Clause 4.3.2.11
Limit	:	EN 300 328 V2.2.2, Clause 4.3.2.11.4
Test suites	:	EN 300 328 V2.2.2, Clause 5.4.11

Test Setup

Date of testing	:	2021.01.29
Test voltage	:	AC230V
Test environment	:	Normal temperature
Operation mode	:	B
Ambient temperature	:	21 °C
Relative humidity	:	60 %
Atmospheric pressure	:	101 kPa

The EUT belongs to receiver category 2 equipment.

For the measurement records, refer to the appendix 1

5.2.3 Geo-location Capability

RESULT:

Not applicable

Test Specification

Test standard : EN 300 328 V2.2.2
Test requirement : EN 300 328 V2.2.2, Clause 4.3.2.12

Exemption Conditions:

This requirement only applies to equipment with geo-location capability as defined in clause 4.3.2.12.1.

Conclusion:

The EUT is adaptive equipment and does not support geo-location capability, hence this requirement is not applicable.

6 Test Results of EMC Requirement

6.1 Test Results of EMISSION

6.1.1 Harmonic Current Emissions on AC Mains

RESULT:

Pass

Test Specification

Test standard	:	EN 301 489-17 V3.2.4:2020 EN IEC 61000-3-2:2019
Basic standard	:	EN 301 489-1 V2.2.3:2019, Clause 8.5
Measured harmonics	:	2 - 40
Classification	:	Class A
Limit	:	EN IEC 61000-3-2:2019, Clause 7.1 Table 1

Test Setup

Date of testing	:	Refer to appendix 1
Test voltage	:	AC 230V, 50Hz
Operation mode	:	B
Test Ports	:	AC Mains
Ambient temperature	:	Refer to appendix 1
Relative humidity	:	Refer to appendix 1
Atmospheric pressure	:	Refer to appendix 1

For the measurement records, refer to the appendix 1.

Prüfbericht - Nr.: CN21IXUA 001

Test Report No.

Seite 23 von 41

Page 23 of 41

6.1.2 Voltage Fluctuations and Flicker on AC Mains

RESULT:

Pass

Test Specification

Test standard	: EN 301 489-17 V3.2.4:2020 EN 61000-3-3:2013+A1
Basic standard	: EN 301 489-1 V2.2.3:2019, Clause 8.6
Frequency range	: 0 – 2 kHz
Limit	: EN 61000-3-3:2013+A1, Clause 5

Test Setup

Date of testing	: Refer to appendix 1
Test voltage	: AC 230V, 50Hz
Operation mode	: B
Test Ports	: AC Mains
Ambient temperature	: Refer to appendix 1
Relative humidity	: Refer to appendix 1
Atmospheric pressure	: Refer to appendix 1

For the measurement records, refer to the appendix 1.

Prüfbericht - Nr.: CN21IXUA 001

Test Report No.

Seite 24 von 41

Page 24 of 41

6.1.3 Conducted Emission on AC Mains

RESULT:

Pass

Test Specification

Test standard	: EN 301 489-17 V3.2.4:2020
Basic standard	: EN 301 489-1 V2.2.3:2019
Test requirement	: EN 301 489-1 V2.2.3:2019, Clause 8.4
Frequency range	: 150 KHz – 30 MHz
Kind of test site	: Shielded Room
Limit	: EN 301 489-1 V2.2.3:2019, Clause 8.4.3.2

Test Setup

Date of testing	: Refer to appendix 1
Test voltage	: AC 230V/50Hz, AC 100V/60Hz
Operation mode	: B
Test Ports	: AC Mains
Ambient temperature	: Refer to appendix 1
Relative humidity	: Refer to appendix 1
Atmospheric pressure	: Refer to appendix 1

For the measurement records, refer to the appendix 1.

6.1.4 Conducted Emission on DC power input/output port

RESULT:

Not applicable

Test Specification

Test standard	: EN 301 489-17 V3.2.4:2020
Basic standard	: EN 301 489-1 V2.2.3:2019
Test requirement	: EN 301 489-1 V2.2.3:2019, Clause 8.3
Frequency range	: 150 KHz – 30 MHz
Kind of test site	: Shielded Room
Limit	: EN 301 489-1 V2.2.3:2019, Clause 8.3.3

Exemption Conditions:

According to the electrical construction of the EUT, there is no DC terminal incorporated. Therefore this test is not applicable for this EUT.

6.1.5 Conducted Emission on Wired network port

RESULT:

Not applicable

Test Specification

Test standard	: EN 301 489-17 V3.2.4:2020
Basic standard	: EN 301 489-1 V2.2.3:2019
Test requirement	: EN 301 489-1 V2.2.3:2019, Clause 8.7
Frequency range	: 150 KHz – 30 MHz
Kind of test site	: Shielded Room
Limit	: EN 301 489-1 V2.2.3:2019, Clause 8.7.3

Exemption Conditions:

According to the electrical construction of the EUT, there is no wired network terminal incorporated. Therefore this test is not applicable for this EUT.

6.1.6 Radiated Emission

RESULT:

Pass

Test Specification

Test standard	: EN 301 489-17 V3.2.4:2020
Basic standard	: EN 301 489-1 V2.2.3:2019
Test requirement	: EN 301 489-1 V2.2.3:2019, Clause 8.2
Classification	: Class B
Frequency range	: 30 MHz – 6 GHz*
Kind of test site	: 3m Semi-anechoic Chamber
Limit	: EN 301 489-1 V2.2.3:2019, Clause 8.2.3

Test Setup

Date of testing	: Refer to appendix 1
Test voltage	: AC 230V/50Hz, AC 100V/60Hz
Operation mode	: B
Test Ports	: Enclosure
Earthing	: Not connected
Ambient temperature	: Refer to appendix 1
Relative humidity	: Refer to appendix 1
Atmospheric pressure	: Refer to appendix 1

*) Since the highest frequency of the internal sources of the EUT is above 1GHz, According to 55032:2015, the measurement shall only be made up to 6 GHz.

For the measurement records, refer to the appendix 1.

6.2 Test Results of IMMUNITY

6.2.1 Radio Frequency Electromagnetic Fields (RS)

RESULT:

Pass

Test Specification

Test standard	: EN 301 489-17 V3.2.4:2020
Basic standard	: EN 301 489-1 V2.2.3:2019 EN 61000-4-3
Test requirement	: EN 301 489-1 V2.2.3:2019, Clause 9.2
Frequency range	: 80 MHz to 6000 MHz
Test level	: 3 V/m, (unmodulated, r.m.s)
Modulation	: 80% AM by a sinusoidal signal of 1kHz
Kind of test site	: 3m Full-anechoic Chamber
Performance criteria	: A (Transmitters: CT & Receivers: CR)

Test Setup

Date of testing	: 2021.01.27
Test voltage	: AC 230V,50Hz
Operation mode	: B
Test Ports	: Enclosure
Ambient temperature	: 22 °C
Relative humidity	: 55 %
Atmospheric pressure	: 101 kPa

Table 8: Test Result of Radio Frequency Electromagnetic Fields (RS)

Test Frequency Band	Test port	Polarity	Location	Actual Performance
80MHz – 1000MHz	Enclosure	Vertical / Horizontal	Front	A*
			Rear	A*
			Left	A*
			Right	A*
1000MHz – 6000MHz	Enclosure	Vertical / Horizontal	Front	A*
			Rear	A*
			Left	A*
			Right	A*

*Remark: No degradation was observed during and after the tests.

6.2.2 Radio Frequency Continuous Conducted (CS)

RESULT:

Pass

Test Specification

Test standard	: EN 301 489-17 V3.2.4:2020
Basic standard	: EN 301 489-1 V2.2.3:2019 EN 61000-4-6
Test requirement	: EN 301 489-1 V2.2.3:2019, Clause 9.5
Frequency range	: 0.15 - 80 MHz
Source impedance	: 150 Ω
Test level	: 3V ms (unmodulated, r.m.s.)
Modulation	: AM 80%, 1 kHz sine-wave
Sweep mode	: Automatic
Sweep rate	: < 1.5×10 ⁻³ decade / sec.
Performance criteria	: A (Transmitters: CT & Receivers: CR)

Test Setup

Date of testing	: 2021.01.27
Input voltage	: AC 230V,50Hz
Operation mode	: B
Test Ports	: AC mains power port**
Earthing	: Not connected
Ambient temperature	: 21 °C
Relative humidity	: 45 %
Atmospheric pressure	: 100 kPa

Table 9: Test Result of Radio Frequency Continuous Conducted (CS)

Coupling point	Application	Level (V(r.m.s))	Remark
Power ports			
AC power port	CDN-M3	3	Applied, *)
DC power port	EM clamp	3	N/A
Signal lines			
Control port	Current Clamp	3	N/A
	EM clamp	3	N/A
Control lines	Current Clamp	3	N/A
	EM clamp	3	N/A

*Remark: No degradation was observed during and after the tests.

6.2.3 Electrostatic Discharge (ESD)

RESULT:

Pass

Test Specification

- Test standard : EN 301 489-17 V3.2.4:2020
- Basic standard : EN 301 489-1 V2.2.3:2019
EN 61000-4-2
- Test requirement : EN 301 489-1 V2.2.3:2019, Clause 9.3
- Discharge impedance : 330 Ω / 150 pF
- Test level : Air discharge: ± 2 kV, ± 4 kV, ± 8 kV
Contact discharge: ± 4 kV
HCP & VCP: ± 4 kV
- Position : All exposed surfaces
- Performance criteria : B (Transmitters: TT & Receivers: TR)

Test Setup

- Date of testing : 2021.01.27
- Input voltage : AC 230V,50Hz
- Operation mode : B
- Test Ports : Enclosure
- Earthing : Not connected
- Ambient temperature : 21 °C
- Relative humidity : 46 %
- Atmospheric pressure : 101.7 kPa

Table 10: Test Result of Electrostatic Discharge (ESD)

Test Level	Location	Actual Performance
± 4 kV / Contact	HCP	A*
	VCP	A*
	Conducted Enclosure	A*
± 2.0kV, ± 4.0kV, ± 8.0kV / Air	Non-conducted Enclosure	A*
	Button	A*
	Slot	A*

*Remark: No degradation was observed during and after the tests.

6.2.4 Electrical Fast Transients (EFT)

RESULT:

Pass

Test Specification

Test standard	: EN 301 489-17 V3.2.4:2020
Basic standard	: EN 301 489-1 V2.2.3:2019 EN 61000-4-4
Test requirement	: EN 301 489-1 V2.2.3:2019, Clause 9.4
Test level	: ± 1.0 kV on AC
Test duration	: 2 minute per level & polarity
Rise time	: 5/50ns
Repetition frequency	: 5 KHz
Performance criteria	: B (Transmitters: TT & Receivers: TR)

Test Setup

Date of testing	: 2021.01.27
Input voltage	: AC 230V,50Hz
Operation mode	: B
Test Ports	: AC mains power input ports**
Earthing	: Not connected
Ambient temperature	: 21 °C
Relative humidity	: 46 %
Atmospheric pressure	: 100kPa

Table 11: Test Result of Electrical Fast Transients (EFT)

Coupling point	Application	Level(kV)	Polarity	Remark
Power ports				
AC power port	Coupling/Decoupling network	1	+	Applied, *)
		1	-	Applied, *)
DC power port	Capacitive Coupling Clamp	0.5	+	N/A
		0.5	-	N/A
Signal lines				
Control port	Capacitive Coupling Clamp	0.5	+	N/A
		0.5	-	N/A
Control lines				
N/A	Capacitive Coupling Clamp	0.5	+	N/A
		0.5	-	N/A

*Remark: No degradation was observed during and after the tests.

6.2.5 Surge

RESULT:

Pass

Test Specification

Test standard : EN 301 489-17 V3.2.4:2020
 Basic standard : EN 301 489-1 V2.2.3:2019
 EN 61000-4-5
 Test requirement : EN 301 489-1 V2.2.3:2019, Clause 9.8
 Test level : ± 1.0 kV line to line
 Repetition rate : Max. 1/min
 Performance criteria : B (Transmitters: TT & Receivers: TR)

Test Setup

Date of testing : 2021.01.27
 Input voltage : AC 230V,50Hz
 Operation mode : B
 Test Ports : ± 1.0 kV line to line on AC
 T_r / T_h : 1,2 / 50 μs
 Earthing : Not connected
 Ambient temperature : 21 °C
 Relative humidity : 46 %
 Atmospheric pressure : 100 kPa

Table 12: Test Result of Surge

Coupling Port	Test Level (±kV)	Coupling Phase	Actual Performance
AC mains power port	± 2.0 kV line to ground & ± 1.0 kV line to line	0	A
		$\pi/2$	A
		π	A
		$3\pi/2$	A

*Remark: No degradation was observed during and after the tests.

6.2.6 Voltage Dips and Interruptions

RESULT:

Pass

Test Specification

Test standard	: EN 301 489-17 V3.2.4:2020
Basic standard	: EN 301 489-1 V2.2.3:2019 EN 61000-4-11
Test requirement	: EN 301 489-1 V2.2.3:2019, Clause 9.7
Test level	: Voltage dips: <input checked="" type="checkbox"/> 0 % residual voltage for 0,5 cycle <input checked="" type="checkbox"/> 0 % residual voltage for 1 cycle <input checked="" type="checkbox"/> 70 % residual voltage for 25 cycles (at 50 Hz) Voltage interruptions: <input checked="" type="checkbox"/> 0 % residual voltage for 250 cycles (at 50 Hz).
Performance criteria	: B (Transmitters: TT & Receivers: TR) C (Transmitters: TT & Receivers: TR) for 250 cycles

Test Setup

Date of testing	: 2021.01.27
Input voltage	: AC 230V,50Hz
Operation mode	: B
Test Ports	: AC mains power port
Earthing	: Not connected
Ambient temperature	: 21 °C
Relative humidity	: 46 %
Atmospheric pressure	: 100 kPa

Table 13: Test Result of Voltage Dips and Interruptions

Coupling Port	Voltage Reduction (%)	Reduction Duration (in Period)	Actual Performance
AC mains power port	100%	0.5	A*
	100%	1	B**
	30%	25	B**
	100%	250	B**

*Remark: No degradation was observed during and after the tests.

**Remark: the EUT was not international transmissions during test, and can be self-recoverable after test.

7 Safety Human Exposure

7.1 Human Exposure to Electromagnetic Fields 10MHz-300GHz

7.1.1 Electromagnetic Fields

RESULT:

Pass

Test Specification

Test standard : EN IEC 62311: 2020

Limit : 61 V/m

Assumed used distance from EUT to Human, 20 cm separation distance warning is required. In this section, the power density at 20 cm location is calculated to examine if it is lower than the limit.

a), Stand-alone

The electric field strength:

$$E = \frac{\sqrt{30 P G_{(\theta, \phi)}}}{r}$$

Antenna gain (G): 1.0dBi

Reference electromagnetic field strength (E): 61 V/m

Distance from EUT to Human (r): 0.20 m

Input power to antenna (P): refer to below table

Table 14: Test Result of Maximum Measured E Field Strength


Test Condition (Temperature)	Antenna Gain (Numeric)	Maximum Output Power (dBm)	Maximum Output Power (mW)	E Field Strength (V/m)	E Field Strength Limit (V/m)	Result
Normal	!Syntax Error, !	11.22	13.24	0.00	61	Pass
Low	!Syntax Error, !	11.19	13.15	0.00	61	Pass
High	!Syntax Error, !	11.20	13.18	0.00	61	Pass
Maximum Measured Value		11.22	13.24	0.00	61	Pass

Conclusion:

The device complies with the EMF directive 1999/519/EC exposure requirements since the maximum Electric Field is less than the limit 61V/m.

8 Photographs of the Test Set-Up


Photograph 1: Set-up for Radio Spectrum Testing



Photograph 2: Set-up for Transmitter & Receiver Spurious Emissions



Photograph 3: Set-up for Harmonic and Flicker




Photograph 4: Set-up for Conducted Emission



Photograph 5: Set-up for Radiated Emission



Photograph 6: Set-up for Radio-frequency Electromagnetic Field Susceptibility



Photograph 7: Set-up for Electrostatic Discharge

⚡ Contact Discharge $\pm 4\text{kV}$


⚡ Air Discharge $\pm 2, 4, 8\text{kV}$



Prüfbericht - Nr.: CN21IXUA 001
Test Report No.

Seite 39 von 41
Page 39 of 41

Photograph 8: Set-up for Conducted Susceptibility (CS)



Photograph 9: Set-up for EFT



Photograph 10: Set-up for Surge



Photograph 11: Set-up for Voltage dips



9 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Measurement Uncertainty.....	7
Table 3: Technical Specification of EUT	8
Table 4: RF Channel and Frequency of General 2.4GHz Wireless	9
Table 5: List of Accessories and Auxiliary Equipment.....	10
Table 6: Test Result of RF Output Power	11
Table 7: Test Result of Power Spectral Density.....	12
Table 8: Test Result of Radio Frequency Electromagnetic Fields (RS).....	27
Table 9: Test Result of Radio Frequency Continuous Conducted (CS).....	28
Table 10: Test Result of Electrostatic Discharge (ESD).....	29
Table 11: Test Result of Electrical Fast Transients (EFT).....	30
Table 12: Test Result of Surge	31
Table 13: Test Result of Voltage Dips and Interruptions	32
Table 14: Test Result of Maximum Measured E Field Strength	33

10 List of Photographs

Photograph 1: Set-up for Radio Spectrum Testing	34
Photograph 2: Set-up for Transmitter & Receiver Spurious Emissions	35
Photograph 3: Set-up for Harmonic and Flicker	36
Photograph 4: Set-up for Conducted Emission	36
Photograph 5: Set-up for Radiated Emission	37
Photograph 6: Set-up for Radio-frequency Electromagnetic Field Susceptibility	38
Photograph 7: Set-up for Electrostatic Discharge	38
Photograph 8: Set-up for Conducted Susceptibility (CS)	39
Photograph 9: Set-up for EFT.....	39
Photograph 10: Set-up for Surge	40
Photograph 11: Set-up for Voltage dips.....	40

Prüfbericht - Nr.:

CN21IXUA 001

Seite 1 von 45

Page 1 of 45

Test Report No.

Waltek Testing Group (Shenzhen) Co., Ltd.

Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
Radiated Test equipment				
Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2020-04-28
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2020-04-28
Amplifier	Agilent	8447F	3113A06717	2020-04-28
Amplifier	C&D	PAP-1G18	2002	2020-04-28
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2019-05-05
Horn Antenna	ETS	3117	00086197	2019-05-05
Conducted Test equipment				
Spectrum Analyzer	Agilent	N9020A	US47140102	2020-04-28
Signal Generator	Agilent	83752A	3610A01453	2020-04-28
Vector Signal Generator	Agilent	N5182A	MY47070202	2020-04-28
Power Sensor	Agilent	U2021XA	MY54250019	2020-04-28
Power Sensor	Agilent	U2021XA	MY54250021	2020-04-28
Simultaneous Sampling	Agilent	U2531A	TW54243509	2020-04-28
temperature and humidity testing machine	KEWEN	GDJS-1000-40	/	2020-10-19
Radiated Emission				
Spectrum Analyzer	Rohde & Schwarz	FSP	836079/035	2020-04-28
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2020-04-28
Amplifier	Agilent	8447F	3113A06717	2020-04-28
Amplifier	C&D	PAP-1G18	2002	2020-04-28
Trilog Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05
Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2019-05-05
Horn Antenna	ETS	3117	00086197	2019-05-05
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	N/A	N/A
Conducted Emission				
EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2020-04-28
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2020-04-28
AC LISN	Schwarz beck	NSLK8126	8126-224	2020-04-28
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	N/A	N/A

Prüfbericht - Nr.:

CN21IXUA 001

Seite 2 von 45

Page 2 of 45

Test Report No.


Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
Harmonics & Flicker				
Digital Power Analyzer	California Instrument	PACS-1	72831	2020-04-28
Power Source	California Instrument	5001iX	25965	2020-04-28
Electrostatic Discharge(ESD)				
ESD Generator	LIOGCEL	ESD-203B	0170901	2020-04-28
Electrical Fast Transient(EFT)				
Transient 2000	EMC PARTNER	TRA2000	863	2020-04-28
Surge				
Transient 2000	EMC PARTNER	TRA2000	863	2020-04-28
Conducted Susceptibility (150kHz-80MHz)				
CONDUCTED IMMUNITY TEST SYSTEM	FRANKONIA	CIT-10/75	126B1247/2013	2021-01-08
Attenuator	EMTEST	MA-5100/6BF2	1009	2020-04-28
CDN	Luthi	L-801M2/M3	2665	2020-04-28
Voltage Dips and Interruptions				
Transient 2000	EMC PARTNER	TRA2000	863	2020-04-28
Radiated Susceptibility				
Anechoic chamber	Albatross Projects	MCDC	----	2020-04-28
Signal Generator	HP	8688B	3438A00604	2020-04-28
Power Meter	KEITHLEY	3500	1162591	2020-04-28
Power Meter	KEITHLEY	3500	1121428	2020-04-28
RF Power Amplifier	MicoTop	MPA-80-1000-250	MPA1906239	2020-04-28
RF Power Amplifier	MicoTop	MPA-80-1000-100	MPA1906238	2020-04-28
Antenna	SCHWARZBECK	STLP 9129	9129 114	N/A

1 RF Test Result


Power Spectral Density


Condition	Mode	Frequency (MHz)	Max PSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
NVNT	ZigBee	2405	9.95	10	Pass
NVNT	ZigBee	2440	9.85	10	Pass
NVNT	ZigBee	2480	9.69	10	Pass

PSD NVNT ZigBee 2405MHz




PSD NVNT ZigBee 2440MHz






Duty Cycle, TX-sequence, TX-gap, Medium Utilisation

DUT Frequency (MHz)	Duty Cycle (%)	Tx-sequence (ms)	Tx Gap (ms)	Medium Utilisation (%)
2405	7.8	1.20	14.08	1.03
2440	7.68	1.20	14.08	1.00
2480	7.81	1.22	14.10	0.97
Limit	≤Maximum value declared by the Manufacturer	≤10	≥3.5	<10




Tx Gap



Date: 22.MAR.2021 16:32:56


Middle

Duty Cycle




Date: 22.MAR.2021 16:45:08

Tx-sequence




Date: 22.MAR.2021 17:09:53

Tx Gap



Date: 22.MAR.2021 16:57:17


High



Date: 22.MAR.2021 16:58:12


Duty Cycle

Tx-sequence



Date: 22.MAR.2021 17:01:50

Tx Gap




Date: 22.MAR.2021 17:02:45

Occupied Channel Bandwidth

Mode	Channel	Measured Frequency (MHz)		Limit (MHz)	Result
		Low	High		
Zigbee	Low	2403.985	2406.035	2400.00~2483.50	Pass
	High	2478.985	2481.035		

OBW NVNT ZigBee 2405MHz


Occupied Channel Bandwidth



RBW: 100 KHz VBW: 300 KHz Sweep Points: 5001

OBW NVNT ZigBee 2480MHz

Occupied Channel Bandwidth




RBW: 100 KHz VBW: 300 KHz Sweep Points: 5001


Transmitter unwanted emissions in the out-of-band domain

DUT Frequency (MHz)	OOB Frequency (MHz)	Level (dBm)	Limit (dBm)	Result
2405	2399.5	-49.561	-10	PASS
2405	2398.5	-51.561	-10	PASS
2405	2398.45	-51.671	-10	PASS
2405	2397.45	-53.111	-20	PASS
2405	2396.45	-54.181	-20	PASS
2405	2396.4	-53.831	-20	PASS
2480	2484	-47.009	-10	PASS
2480	2485	-50.229	-10	PASS
2480	2485.05	-50.089	-10	PASS
2480	2486.05	-51.169	-20	PASS
2480	2487.05	-52.249	-20	PASS
2480	2487.1	-52.369	-20	PASS

Transmitter unwanted emissions in the out-of-band domain




Transmitter unwanted emissions in the out-of-band domain




Transmitter Unwanted Emissions in the Spurious Domain


➤ Below 1GHz




No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	32.4059	-66.75	-2.22	-68.97	-36.00	-32.97	ERP
2	48.5016	-70.63	0.19	-70.44	-54.00	-16.44	ERP
3	105.6415	-70.64	-1.51	-72.15	-54.00	-18.15	ERP
4	247.6819	-72.73	0.76	-71.97	-36.00	-35.97	ERP
5	513.6331	-74.37	7.68	-66.69	-54.00	-12.69	ERP
6	975.7529	-75.93	13.29	-62.64	-36.00	-26.64	ERP



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	32.4059	-64.48	-2.22	-66.70	-36.00	-30.70	ERP
2	49.0145	-69.90	0.21	-69.69	-54.00	-15.69	ERP
3	111.7380	-72.06	-1.68	-73.74	-54.00	-19.74	ERP
4	277.0935	-72.02	1.19	-70.83	-36.00	-34.83	ERP
5	489.0269	-74.27	7.42	-66.85	-54.00	-12.85	ERP
6	893.8567	-76.57	13.10	-63.47	-36.00	-27.47	ERP




No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	32.2925	-68.21	-2.23	-70.44	-36.00	-34.44	ERP
2	45.0583	-70.34	0.00	-70.34	-36.00	-34.34	ERP
3	106.0126	-70.62	-1.51	-72.13	-54.00	-18.13	ERP
4	277.0935	-71.69	1.19	-70.50	-36.00	-34.50	ERP
5	497.6765	-74.93	7.68	-67.25	-54.00	-13.25	ERP
6	948.7610	-74.60	13.19	-61.41	-36.00	-25.41	ERP



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	32.4059	-64.94	-2.22	-67.16	-36.00	-31.16	ERP
2	57.1914	-70.99	-1.17	-72.16	-54.00	-18.16	ERP
3	119.0180	-71.80	-2.40	-74.20	-36.00	-38.20	ERP
4	295.1469	-74.58	2.53	-72.05	-36.00	-36.05	ERP
5	554.8254	-74.83	8.24	-66.59	-54.00	-12.59	ERP
6	900.1474	-76.26	13.35	-62.91	-36.00	-26.91	ERP

➤ Above 1GHz




No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	4810.000	-56.20	7.29	-48.91	-30.00	-18.91	ERP
2	7215.000	-56.71	9.60	-47.11	-30.00	-17.11	ERP
3	9620.000	-57.40	13.55	-43.85	-30.00	-13.85	ERP

Prüfbericht - Nr.:
Test Report No.

CN21IXUA 001

Seite 16 von 45
Page 16 of 45




No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	4810.000	-56.37	7.29	-49.08	-30.00	-19.08	ERP
2	7215.000	-57.39	9.60	-47.79	-30.00	-17.79	ERP
3	9620.000	-57.17	13.55	-43.62	-30.00	-13.62	ERP

Prüfbericht - Nr.:
Test Report No.

CN21IXUA 001

Seite 17 von 45
Page 17 of 45




No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	4960.000	-55.97	7.39	-48.58	-30.00	-18.58	ERP
2	7440.000	-57.75	9.66	-48.09	-30.00	-18.09	ERP
3	9920.000	-56.85	13.99	-42.86	-30.00	-12.86	ERP

Prüfbericht - Nr.:
Test Report No.



CN21IXUA 001

Seite 18 von 45
Page 18 of 45



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	4960.000	-55.94	7.39	-48.55	-30.00	-18.55	ERP
2	7440.000	-56.82	9.66	-47.16	-30.00	-17.16	ERP
3	9920.000	-56.02	13.99	-42.03	-30.00	-12.03	ERP


➤ **Conducted Transmitter Spurious Emission:**




Note 1: Testing is carried out with frequency rang 30MHz to 12.75GHz, which emissions are too small are not list above.

Receiver Spurious Emissions

➤ Below 1GHz



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	32.4059	-65.94	-2.22	-68.16	-57.00	-11.16	ERP
2	50.4089	-71.62	0.15	-71.47	-57.00	-14.47	ERP
3	111.3468	-70.96	-1.65	-72.61	-57.00	-15.61	ERP
4	277.0935	-72.36	1.19	-71.17	-57.00	-14.17	ERP
5	531.9635	-74.91	7.73	-67.18	-57.00	-10.18	ERP
6	912.8620	-76.00	13.51	-62.49	-57.00	-5.49	ERP




No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	32.4059	-64.77	-2.22	-66.99	-57.00	-9.99	ERP
2	54.2610	-71.05	-0.94	-71.99	-57.00	-14.99	ERP
3	129.0146	-70.09	-4.90	-74.99	-57.00	-17.99	ERP
4	325.5958	-72.72	2.87	-69.85	-57.00	-12.85	ERP
5	515.4374	-74.70	7.68	-67.02	-57.00	-10.02	ERP
6	893.8567	-75.24	13.10	-62.14	-57.00	-5.14	ERP


Prüfbericht - Nr.:
Test Report No.

CN21IXUA 001

Seite 22 von 45
Page 22 of 45



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	32.5198	-68.29	-2.21	-70.50	-57.00	-13.50	ERP
2	51.8430	-69.91	-0.24	-70.15	-57.00	-13.15	ERP
3	118.1862	-70.52	-2.32	-72.84	-57.00	-15.84	ERP
4	259.2338	-72.89	0.96	-71.93	-57.00	-14.93	ERP
5	495.9344	-74.50	7.63	-66.87	-57.00	-9.87	ERP
6	884.5029	-75.09	12.72	-62.37	-57.00	-5.37	ERP




No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	32.4059	-63.01	-2.22	-65.23	-57.00	-8.23	ERP
2	50.7637	-69.82	0.05	-69.77	-57.00	-12.77	ERP
3	102.3597	-72.17	-1.51	-73.68	-57.00	-16.68	ERP
4	317.7011	-73.69	2.86	-70.83	-57.00	-13.83	ERP
5	584.7895	-75.96	9.48	-66.48	-57.00	-9.48	ERP
6	958.7943	-75.94	13.20	-62.74	-57.00	-5.74	ERP

Prüfbericht - Nr.:
Test Report No.


CN21IXUA 001

Seite 24 von 45
Page 24 of 45

➤ Above 1GHz



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	4810.000	-67.67	7.29	-60.38	-47.00	-13.38	ERP
2	7215.000	-67.38	9.60	-57.78	-47.00	-10.78	ERP
3	9620.000	-68.85	13.55	-55.30	-47.00	-8.30	ERP




No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	4810.000	-67.68	7.29	-60.39	-47.00	-13.39	ERP
2	7215.000	-68.37	9.60	-58.77	-47.00	-11.77	ERP
3	9620.000	-68.49	13.55	-54.94	-47.00	-7.94	ERP


Prüfbericht - Nr.:
Test Report No.

CN21IXUA 001

Seite 26 von 45
Page 26 of 45





No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	4960.000	-67.27	7.39	-59.88	-47.00	-12.88	ERP
2	7440.000	-68.11	9.66	-58.45	-47.00	-11.45	ERP
3	9920.000	-67.30	13.99	-53.31	-47.00	-6.31	ERP



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	4960.000	-67.82	7.39	-60.43	-47.00	-13.43	ERP
2	7440.000	-67.34	9.66	-57.68	-47.00	-10.68	ERP
3	9920.000	-66.61	13.99	-52.62	-47.00	-5.62	ERP

Conducted Receiver Spurious Emission:



Note 1: Testing is carried out with frequency rang 30MHz to 12.75GHz, which emissions are too small are not list above.

Prüfbericht - Nr.:

CN21IXUA 001

Seite 29 von 45

Test Report No.

Page 29 of 45

Receiver Blocking

The product is receiver category 2

Mode/ Channel	Wanted signal power (dBm)	Blocking signal Frequency (MHz)	Blocking signal power (dBm)	Test PER(%)	Limit(%)	Result
ZigBee- Low channel	-66	2380	-34	1.67	<10	Pass
		2300				
ZigBee- High channel	-66	2504	-34	2.06	<10	Pass
		2584				

OBW=2.06MHz


2 EMC Test Result

Harmonics – Class-A per Ed. Ed. 5.0 (2018)(Run time)

Test category: Class-A per Ed. 5.0 (2018) (European limits) Test Margin: 100
Test date: 2021-1-18 Start time: pm 04:49:28 End time: pm 04:52:10
Test duration (min): 2.5 Data file name: H-000559.cts_data
Comment:
Customer:


Test Result: Pass Source qualification: Normal

Current & voltage waveforms



Harmonics and Class A limit line

European Limits



Test result: Pass Worst harmonics H0-0.0% of 150% limit, H0-0% of 100% limit

Prüfbericht - Nr.:

CN21IXUA 001

Seite 31 von 45

Test Report No.

Page 31 of 45

Current Test Result Summary (Run time)

Test category: Class-A per Ed. 5.0 (2018) (European limits) Test Margin: 100
 Test date: 2021-1-18 Start time: pm 04:49:28 End time: pm 04:52:10
 Test duration (min): 2.5 Data file name: H-000559.cts_data
 Comment:
 Customer:

Test Result: Pass Source qualification: Normal
 THC(A): 0.007 I-THD(%): 2.6 POHC(A): 0.002 POHC Limit(A): 0.251

Highest parameter values during test:

V_RMS (Volts): 229.96 Frequency(Hz): 50.00
 I_Peak (Amps): 0.476 I_RMS (Amps): 0.287
 I_Fund (Amps): 0.287 Crest Factor: 1.659
 Power (Watts): 65.9 Power Factor: 0.999

Harm#	Harms(avg)	100%Limit	%of Limit	Harms(max)	150%Limit	%of Limit	Status
2	0.002	1.080	N/A	0.002	1.620	N/A	Pass
3	0.004	2.300	N/A	0.005	3.450	N/A	Pass
4	0.002	0.430	N/A	0.002	0.645	N/A	Pass
5	0.002	1.140	N/A	0.002	1.710	N/A	Pass
6	0.002	0.300	N/A	0.002	0.450	N/A	Pass
7	0.002	0.770	N/A	0.002	1.155	N/A	Pass
8	0.001	0.230	N/A	0.002	0.345	N/A	Pass
9	0.001	0.400	N/A	0.002	0.600	N/A	Pass
10	0.001	0.184	N/A	0.002	0.276	N/A	Pass
11	0.001	0.330	N/A	0.002	0.495	N/A	Pass
12	0.001	0.153	N/A	0.001	0.230	N/A	Pass
13	0.001	0.210	N/A	0.001	0.315	N/A	Pass
14	0.001	0.131	N/A	0.001	0.197	N/A	Pass
15	0.001	0.150	N/A	0.001	0.225	N/A	Pass
16	0.001	0.115	N/A	0.001	0.173	N/A	Pass
17	0.001	0.132	N/A	0.001	0.198	N/A	Pass
18	0.001	0.102	N/A	0.001	0.153	N/A	Pass
19	0.001	0.118	N/A	0.001	0.178	N/A	Pass
20	0.001	0.092	N/A	0.001	0.138	N/A	Pass
21	0.001	0.107	N/A	0.001	0.161	N/A	Pass
22	0.001	0.084	N/A	0.001	0.125	N/A	Pass
23	0.001	0.098	N/A	0.001	0.147	N/A	Pass
24	0.001	0.077	N/A	0.001	0.115	N/A	Pass
25	0.001	0.090	N/A	0.001	0.135	N/A	Pass
26	0.001	0.071	N/A	0.001	0.107	N/A	Pass
27	0.001	0.083	N/A	0.001	0.125	N/A	Pass
28	0.001	0.066	N/A	0.001	0.099	N/A	Pass
29	0.001	0.078	N/A	0.001	0.116	N/A	Pass
30	0.001	0.061	N/A	0.001	0.092	N/A	Pass
31	0.000	0.073	N/A	0.001	0.109	N/A	Pass
32	0.000	0.058	N/A	0.001	0.086	N/A	Pass
33	0.000	0.068	N/A	0.000	0.102	N/A	Pass
34	0.000	0.054	N/A	0.000	0.081	N/A	Pass
35	0.000	0.064	N/A	0.000	0.096	N/A	Pass
36	0.000	0.051	N/A	0.000	0.077	N/A	Pass
37	0.000	0.061	N/A	0.000	0.091	N/A	Pass
38	0.000	0.048	N/A	0.000	0.073	N/A	Pass
39	0.000	0.058	N/A	0.000	0.087	N/A	Pass
40	0.000	0.046	N/A	0.000	0.069	N/A	Pass

Prüfbericht - Nr.:

CN21IXUA 001

Seite 32 von 45

Test Report No.

Page 32 of 45

Voltage Source Verification Data (Run time)

Test category: Class-A per Ed. 5.0 (2018) (European limits) Test Margin: 100
 Test date: 2021-1-18 Start time: pm 04:49:28 End time: pm 04:52:10
 Test duration (min): 2.5 Data file name: H-000559.cts_data
 Comment:
 Customer:

Test Result: Pass Source qualification: Normal

Highest parameter values during test:

Voltage (Vrms): 229.96 Frequency(Hz): 50.00
 I_Peak (Amps): 0.476 I_RMS (Amps): 0.287
 I_Fund (Amps): 0.287 Crest Factor: 1.659
 Power (Watts): 65.9 Power Factor: 0.999

Harm#	Harmonics V-rms	Limit V-rms	% of Limit	Status
2	0.058	0.460	12.59	OK
3	0.499	2.069	24.12	OK
4	0.056	0.460	12.12	OK
5	0.062	0.920	6.73	OK
6	0.031	0.460	6.78	OK
7	0.021	0.690	3.00	OK
8	0.016	0.460	3.56	OK
9	0.010	0.460	2.19	OK
10	0.012	0.460	2.63	OK
11	0.013	0.230	5.57	OK
12	0.010	0.230	4.16	OK
13	0.012	0.230	5.36	OK
14	0.005	0.230	2.14	OK
15	0.010	0.230	4.42	OK
16	0.008	0.230	3.59	OK
17	0.012	0.230	5.28	OK
18	0.012	0.230	5.38	OK
19	0.012	0.230	5.26	OK
20	0.015	0.230	6.46	OK
21	0.010	0.230	4.54	OK
22	0.005	0.230	1.98	OK
23	0.005	0.230	2.38	OK
24	0.003	0.230	1.51	OK
25	0.006	0.230	2.74	OK
26	0.004	0.230	1.65	OK
27	0.006	0.230	2.82	OK
28	0.005	0.230	2.10	OK
29	0.008	0.230	3.36	OK
30	0.004	0.230	1.65	OK
31	0.005	0.230	2.34	OK
32	0.004	0.230	1.56	OK
33	0.005	0.230	2.05	OK
34	0.003	0.230	1.21	OK
35	0.005	0.230	2.17	OK
36	0.003	0.230	1.33	OK
37	0.005	0.230	2.34	OK
38	0.003	0.230	1.15	OK
39	0.006	0.230	2.54	OK
40	0.009	0.230	3.80	OK

Flicker Test Summary per EN/IEC61000-3-3 Ed. 3.0 (2013) (Run time)

Prüfbericht - Nr.:

CN21IXUA 001

Seite 33 von 45

Test Report No.

Page 33 of 45


Test category: All parameters (European limits) Test Margin: 100
Test date: 2021-1-18 Start time: pm 04:36:05 End time: pm 04:46:32
Test duration (min): 10 Data file name: F-000558.cts_data
Comment:
Customer:

Test Result: Pass


Status: Test Completed

Pst_i and limit line

European Limits



Plt and limit line



Parameter values recorded during the test:

Vrms at the end of test (Volt):	229.79			
T-max (mS):	0	Test limit (mS):	500.0	Pass
Highest dc (%):	0.00	Test limit (%):	3.30	Pass
Highest dmax (%):	0.00	Test limit (%):	4.00	Pass
Highest Pst (10 min. period):	0.064	Test limit:	1.000	Pass
Highest Plt (2 hr. period):	0.028	Test limit:	0.650	Pass

Prüfbericht - Nr.:

CN21IXUA 001


Seite 34 von 45

Page 34 of 45

Test Report No.

AC100V 60Hz

Test mode:	TM1	Polarity:	Neutral
------------	-----	-----------	---------




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1660	20.05	10.26	30.31	55.15	-24.84	AVG
2	0.1700	34.84	10.25	45.09	64.96	-19.87	QP
3*	0.8980	21.88	10.22	32.10	46.00	-13.90	AVG
4	0.9060	28.01	10.22	38.23	56.00	-17.77	QP
5	2.2100	15.72	10.29	26.01	46.00	-19.99	AVG
6	2.2420	22.55	10.29	32.84	56.00	-23.16	QP

Prüfbericht - Nr.:
Test Report No.

CN21IXUA 001

Seite 35 von 45
Page 35 of 45

Test mode:	TM1	Polarity:	Line
------------	-----	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1700	35.81	10.25	46.06	64.96	-18.90	QP
2	0.1700	20.18	10.25	30.43	54.96	-24.53	AVG
3*	0.8980	18.99	10.22	29.21	46.00	-16.79	AVG
4	0.9060	26.89	10.22	37.11	56.00	-18.89	QP
5	2.1820	20.98	10.29	31.27	56.00	-24.73	QP
6	2.2420	12.52	10.29	22.81	46.00	-23.19	AVG


Prüfbericht - Nr.:
Test Report No.

CN21IXUA 001

Seite 36 von 45
Page 36 of 45

AC 230V, 50Hz

Test mode:	TM2	Polarity:	Neutral
------------	-----	-----------	---------




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1700	32.94	10.25	43.19	64.96	-21.77	QP
2	0.1860	17.99	10.26	28.25	54.21	-25.96	AVG
3*	1.1140	21.76	10.21	31.97	46.00	-14.03	AVG
4	1.2140	28.47	10.22	38.69	56.00	-17.31	QP
5	3.4900	18.86	10.25	29.11	46.00	-16.89	AVG
6	3.7700	25.31	10.25	35.56	56.00	-20.44	QP

Prüfbericht - Nr.:
Test Report No.

CN21IXUA 001

Seite 37 von 45
Page 37 of 45

Test mode:	TM2	Polarity:	Line
------------	-----	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1539	33.04	10.25	43.29	65.78	-22.49	QP
2	0.1780	16.51	10.26	26.77	54.57	-27.80	AVG
3*	3.6540	15.30	10.25	25.55	46.00	-20.45	AVG
4	3.7060	21.65	10.25	31.90	56.00	-24.10	QP
5	5.9740	20.45	10.23	30.68	60.00	-29.32	QP
6	6.1340	13.77	10.24	24.01	50.00	-25.99	AVG

Prüfbericht - Nr.:

CN21IXUA 001


Seite 38 von 45

Test Report No.

Page 38 of 45

➤ 30MHz to 1GHz
AC100V 60Hz

Test mode:	TM1	Polarity:	Horizontal
------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	39.1616	36.61	-12.30	24.31	40.00	-15.69	QP
2	58.8185	36.18	-12.97	23.21	40.00	-16.79	QP
3	99.1797	33.69	-13.45	20.24	40.00	-19.76	QP
4	170.7926	35.73	-14.97	20.76	40.00	-19.24	QP
5	375.9385	30.50	-7.16	23.34	47.00	-23.66	QP
6	651.9417	29.91	-2.33	27.58	47.00	-19.42	QP

Prüfbericht - Nr.:
Test Report No.

CN21IXUA 001

Seite 39 von 45
Page 39 of 45

Test mode:	TM1	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	43.6584	35.73	-11.84	23.89	40.00	-16.11	QP
2	51.4807	36.15	-11.96	24.19	40.00	-15.81	QP
3	107.5101	33.59	-13.32	20.27	40.00	-19.73	QP
4	259.2338	35.37	-10.85	24.52	47.00	-22.48	QP
5	517.2480	29.56	-4.14	25.42	47.00	-21.58	QP
6	900.1474	30.14	1.55	31.69	47.00	-15.31	QP

Prüfbericht - Nr.:

CN21IXUA 001


Seite 40 von 45

Test Report No.

Page 40 of 45

AC 230V, 50Hz

Test mode:	TM2	Polarity:	Horizontal
------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	44.7434	36.21	-11.81	24.40	40.00	-15.60	QP
2	52.2079	34.92	-12.15	22.77	40.00	-17.23	QP
3	94.7601	34.44	-14.19	20.25	40.00	-19.75	QP
4	238.3102	30.56	-11.50	19.06	47.00	-27.94	QP
5	392.0951	30.44	-6.69	23.75	47.00	-23.25	QP
6	601.4265	29.62	-1.94	27.68	47.00	-19.32	QP

Prüfbericht - Nr.:
Test Report No.

CN21IXUA 001

Seite 41 von 45
Page 41 of 45

Test mode:	TM2	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	38.4809	37.02	-12.56	24.46	40.00	-15.54	QP
2	51.1209	35.05	-11.85	23.20	40.00	-16.80	QP
3	99.5281	33.44	-13.39	20.05	40.00	-19.95	QP
4	257.4222	32.05	-10.87	21.18	47.00	-25.82	QP
5	524.5541	30.31	-4.18	26.13	47.00	-20.87	QP
6	881.4067	29.50	0.79	30.29	47.00	-16.71	QP

Prüfbericht - Nr.:

CN21IXUA 001


Seite 42 von 45

Page 42 of 45

Test Report No.

➤ Above 1GHz
AC100V 60Hz

Test mode:	TM1	Polarity:	Horizontal
------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1882.294	54.59	-8.71	45.88	70.00	-24.12	peak
2	1895.833	41.57	-8.60	32.97	50.00	-17.03	AVG
3	2337.996	53.93	-9.61	44.32	70.00	-25.68	peak
4	2337.996	42.08	-9.61	32.47	50.00	-17.53	AVG
5	3442.900	53.94	-7.37	46.57	74.00	-27.43	peak
6	3480.112	41.49	-7.25	34.24	54.00	-19.76	AVG

Prüfbericht - Nr.:
Test Report No.

CN21IXUA 001

Seite 43 von 45
Page 43 of 45

Test mode:	TM1	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1895.832	41.41	-8.60	32.81	50.00	-17.19	AVG
2	1926.652	53.58	-9.02	44.56	70.00	-25.44	peak
3	2471.533	57.20	-9.34	47.86	70.00	-22.14	peak
4	2471.533	43.64	-9.34	34.30	50.00	-15.70	AVG
5	3442.900	53.62	-7.37	46.25	74.00	-27.75	peak
6	3480.112	41.51	-7.25	34.26	54.00	-19.74	AVG


Prüfbericht - Nr.:
Test Report No.

CN21IXUA 001

Seite 44 von 45
Page 44 of 45

AC 230V, 50Hz

Test mode:	TM2	Polarity:	Horizontal
------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1895.833	53.10	-8.60	44.50	70.00	-25.50	peak
2	1895.833	41.55	-8.60	32.95	50.00	-17.05	AVG
3	3097.515	52.59	-8.36	44.23	74.00	-29.77	peak
4	3424.443	41.38	-7.43	33.95	54.00	-20.05	AVG
5	4291.775	54.07	-5.55	48.52	74.00	-25.48	peak
6	4330.397	40.96	-5.40	35.56	54.00	-18.44	AVG

Prüfbericht - Nr.:
Test Report No.

CN21IXUA 001

Seite 45 von 45
Page 45 of 45

Test mode:	TM2	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1865.506	54.11	-8.86	45.25	70.00	-24.75	peak
2	1885.669	41.60	-8.68	32.92	50.00	-17.08	AVG
3	3170.512	56.19	-8.15	48.04	74.00	-25.96	peak
4	3256.879	40.48	-7.90	32.58	54.00	-21.42	AVG
5	4677.225	40.59	-4.60	35.99	54.00	-18.01	AVG
6	4685.613	52.46	-4.60	47.86	74.00	-26.14	peak