



Shenzhen GTI Technology Co., Ltd.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park,
Shenzhen, Guangdong, China
Tel: +86-755-27559792
Fax: +86-755-86116468

TEST REPORT

Product Name : Wireless Mini Switch

Trademark : AQara

Model/Type reference : WXKG11LM

Listed Model(s)..... : /

Test Standards : **EN62479:2010**

Applicant : Lumi United Technology Co., Ltd.

Address of Applicant..... : 8th Floor, JinQi Wisdom Valley, No.1 Tangling Road, Liuxian Ave,
Taoyuan Residential District, Nanshan District, Shenzhen, China.

Date of Receipt : Nov. 7, 2017

Date of Test Date : Nov. 7, 2017 - Nov. 12, 2017

Data of Issue. : Nov. 14, 2017

| | |
|--------------------|---------------|
| Test result | Pass * |
|--------------------|---------------|

* In the configuration tested, the EUT complied with the standards specified above



The CE mark as shown above can be used, under the responsibility of the manufacturer, after completion of an EC Declaration of Conformity and compliance with all relevant EC Directives. The protection requirements with respect to electromagnetic compatibility contained in Directive 2014/53/EU are considered.

| GENERAL DESCRIPTION OF EUT | |
|----------------------------|---|
| Equipment: | Wireless Mini Switch |
| Model Name: | WXKG11LM |
| Manufacturer: | Lumi United Technology Co., Ltd. |
| Manufacturer Address: | 8th Floor, JinQi Wisdom Valley, No.1 Tangling Road, Liuxian Ave, Taoyuan Residential District, Nanshan District, Shenzhen, China. |
| Power Rating: | Input: DC 3V,25mA. (This is powered by the CR2032 battery) |

Compiled By: Zaki Zhang
(Zaki Zhang)

Reviewed By: Cavin Shi
(Cavin Shi)

Approved By: Walter Chen

It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by GTI. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to GTI within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.

Table of Contents

Page

| | | |
|------|--------------------------------|---|
| 1. | GENERAL INFORMATION | 4 |
| 1.1. | ENVIRONMENTAL CONDITIONS | 4 |
| 1.2. | PRODUCT DESCRIPTION | 4 |
| 1.3. | TEST FACILITY | 5 |
| 2. | METHOD OF MEASUREMENT | 6 |
| 3. | TEST RESULT | 7 |



1. GENGNERAL INFORMATION

1.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

| | |
|---------------------|--------|
| Normal Temperature: | 25°C |
| Relative Humidity: | 55 % |
| Air Pressure: | 101KPa |

1.2. Product Description

| | |
|-----------------------|---|
| Product Name: | Wireless Mini Switch |
| Model/Type reference: | WXKG11LM |
| Power supply: | DC 3V,25mA. (This is powered by the CR2032 battery) |
| FHSS | |
| Modulation: | O-QPSK |
| Operation frequency: | 2405MHz to 2480MHz |
| Channel number: | 16 |
| Channel Separation: | 5 MHz |
| Antenna type: | PCB Antenna |
| Antenna gain: | 2.00dBi |

Note: For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

1.3. Test Facility

1.3.1 Address of the test laboratory

Shenzhen General Testing & Inspection Technology Co., Ltd.

Add: 1F, 2 Block, Jiaquan Building, Guanlan High-tech Park Baoan District, Shenzhen, Guangdong, China

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 9783A

The 3m alternate test site of Shenzhen GTI Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 9783A on Jan, 2016.



2. Method of measurement

Applicable Standard

EN62479_2010: Assessment of the compliance of low-power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)

EMF Assessment Method

According to the EN62479 Annex A.2

Table A.1 – Example values of SAR-based P_{max} for some cases described by ICNIRP, IEEE Std C95.1-1999 and IEEE Std C95.1-2005

| Guideline / Standard | SAR limit, SAR_{max} W/kg | Averaging mass, m g | P_{max} mW | Exposure tier ^a | Region of body ^a |
|-------------------------|--------------------------------|--------------------------|-----------------|----------------------------|------------------------------------|
| ICNIRP [1] | 2 | 10 | 20 | General public | Head and trunk |
| | 4 | 10 | 40 | General public | Limbs |
| | 10 | 10 | 100 | Occupational | Head and trunk |
| | 20 | 10 | 200 | Occupational | Limbs |
| IEEE Std C95.1-1999 [2] | 1,6 | 1 | 1,6 | Uncontrolled environment | Head, trunk, arms, legs |
| | 4 | 10 | 40 | Uncontrolled environment | Hands, wrists, feet and ankles |
| | 8 | 1 | 8 | Controlled environment | Head, trunk, arms, legs |
| | 20 | 10 | 200 | Controlled environment | Hands, wrists, feet and ankles |
| IEEE Std C95.1-2005 [3] | 2 | 10 | 20 | Action level | Body except extremities and pinnae |
| | 4 | 10 | 40 | Action level | Extremities and pinnae |
| | 10 | 10 | 100 | Controlled environment | Body except extremities and pinnae |
| | 20 | 10 | 200 | Controlled environment | Extremities and pinnae |

^a Consult the appropriate standard for more information and definitions of terms.

3. Test Result

| Mode | Max Measured power (dBm) | Conducted Output Power | | | Limit |
|--------|--------------------------|------------------------|------------|------|-------|
| | | Antenna Gain (dBi) | EIRP (dBm) | (mW) | |
| O-QPSK | 7.01 | 2.00 | 9.01 | 7.96 | 20 |

Note: 1. because the output power of theEUT is less than 20mW (13dBm), so standalone SAR are exempt.

*****THE END*****

